SPECIFICATION SHEET Agent: Graham Lloyd EMPACHER



customer:	nation:		date:	
phone :	addr	ess:		
fax :	sign	ature of custom	ner:	
e-mail :	requ	ested date of d	elivery:	
type of boat:	mould no.:	rigging:		
crew weight (averag		normal: pt stb	italien: italien: or: stb pt stb stroke: stroke: stroke	: :
rigger sweep:	□X □ C □ R □ C □ R	\circ		
coxswain:	sitting in stern (four, eight) lying in bow (pair, four)	bow 1	bow bow bow	
section: yes / no	(seat no. 6 / 7)	1 (3 3 3	2
length of tracks:	standard = 83cm			
(track without stoppers)	other length:	sketch for out	rigger dimensions:	
sliding seat		(1)	pin Spread:	
☐ carbon without holes	☐ standard height		b) middle of boat-pin	
new model 2019	☐ medium (5mm lower)	201		
☐ carbon with holes	□ low (10mm lower)	$\setminus ($	Height:	
	☐ high (5mm higher)		a) deepest point of seat (1) to base of oarlock (2)	
□ cedar wood	□ extra high (10mm higher)		(2)	
with holes	height adjustable	, -		
gates: Emp. insert		\		
gatoor Emp. moort			a de la companya de l	
other:				
outrigger dimensions (s. sketch): oarlock set in middle position		optionals:		
Carlock Set III IIIIddie po	Sition	-	on profiles at canvas	
	scull sweep		carbon fin rudder	
a) height starboard	Споср	_	vice integrated inside canvas	
(left hand):	cm	☐ Textrem de		
height portside	cm	☐ Olympic Ed		
(right hand):	cm		ks and carbon layer inside	
			rdered with round carbon profiles at canvas)	
b) spread	cmcm	☐ full carbon s	stretcher with 4° vertical curve	
steering shoe	☐ right foot	☐ carbon shoe	eplate for variable shoe angle	
seat no.:	🗆 left foot	☐ shoeplate c	arbon with 4° □ or 6° □	
	seat no.:	☐ additional w		
shoe sizes:	1 = 5 =	remarks / spec	ial requests:	
(EU sizes)	2 = 6 =			
	3 = 7 =			
	4 = 8 =			
electr. system:				
CoxBox cplt.	☐ CoxBox GPS cplt.			
CoxBox wiring only	•			
☐ StrokeCoach Surge☐ SpeedCoach GPS2	☐ SpeedCoach GPS2 + Tr. P.			
· ·	StrokeC. T-bracket A-bracket			
boat cover:	polyester, PVC coated, with zip			
cover for outrigger:	qty.:			